

# Safety Data Sheet

## WABO SILICONE SEAL PART A

Revision date : 2015/09/10  
Version: 3.0

Page: 1/10  
(30574095/SDS\_GEN\_CA/EN)

### 1. Identification

#### Product identifier used on the label

## WABO SILICONE SEAL PART A

#### Recommended use of the chemical and restriction on use

Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF Canada Inc.  
100 Milverton Drive  
Mississauga, ON L5R 4H1, CANADA

Telephone: +1 289 360-1300

#### Emergency telephone number

CANUTEC (reverse charges): (613) 996-6666  
BASF HOTLINE: (800) 454-COPE (2673)

#### Other means of identification

Chemical family: No data available.

---

### 2. Hazards Identification

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

##### Classification of the product

Skin Sens.	1B	Skin sensitization
Repr.	1B (unborn child)	Reproductive toxicity
STOT RE	2	Specific target organ toxicity — repeated exposure
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

##### Label elements

# Safety Data Sheet

## WABO SILICONE SEAL PART A

Revision date : 2015/09/10  
Version: 3.0

Page: 2/10  
(30574095/SDS\_GEN\_CA/EN)

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H317	May cause an allergic skin reaction.
H360	May damage the unborn child.
H373	May cause damage to organs (Central nervous system) through prolonged or repeated exposure.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P260	Do not breathe dust/gas/mist/vapours.
P273	Avoid release to the environment.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P272	Contaminated work clothing should not be allowed out of the workplace.

Precautionary Statements (Response):

P314	Get medical advice/attention if you feel unwell.
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.
P308 + P311	IF exposed or concerned: Call a POISON CENTER or doctor/physician.
P362 + P364	Take off contaminated clothing and wash before reuse.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

### According to Controlled Products Regulations (CPR) (SOR/88-66)

#### Emergency overview

IRRITANT.  
SENSITIZER.  
Contains a suspect teratogen.

---

### 3. Composition / Information on Ingredients

#### According to Hazardous Products Regulations (HPR) (SOR/2015-17)

# Safety Data Sheet

## WABO SILICONE SEAL PART A

Revision date : 2015/09/10  
Version: 3.0

Page: 3/10  
(30574095/SDS\_GEN\_CA/EN)

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
63148-62-9	>= 25.0 - < 50.0%	Dimethyl silicones and siloxanes
1317-65-3	>= 10.0 - < 15.0%	Limestone
108-88-3	>= 1.0 - < 3.0%	Toluene
34206-40-1	>= 1.0 - < 3.0%	2-Butanone, 2,2',2'',2'''-(O,O',O'',O'''-silanetetrayltetraoxime)
1067-33-0	>= 0.1 - < 0.2%	Stannane, bis(acetyloxy)dibutyl-
13463-67-7	>= 0.1 - <= 1.0%	Titanium dioxide

### According to Controlled Products Regulations (CPR) (SOR/88-66)

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
63148-62-9	>= 25.0 - < 50.0%	Dimethyl silicones and siloxanes
1317-65-3	>= 10.0 - < 15.0%	Limestone
108-88-3	>= 1.0 - < 3.0%	Toluene
34206-40-1	>= 1.0 - < 3.0%	2-Butanone, 2,2',2'',2'''-(O,O',O'',O'''-silanetetrayltetraoxime)
1067-33-0	>= 0.1 - < 0.2%	Stannane, bis(acetyloxy)dibutyl-
13463-67-7	>= 0.1 - <= 1.0%	Titanium dioxide

## 4. First-Aid Measures

### Description of first aid measures

#### General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

#### If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

#### If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

#### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

#### If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

### Most important symptoms and effects, both acute and delayed

Symptoms: skin irritation, allergic symptoms

Hazards: No applicable information available.

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

# Safety Data Sheet

## WABO SILICONE SEAL PART A

Revision date : 2015/09/10  
Version: 3.0

Page: 4/10  
(30574095/SDS\_GEN\_CA/EN)

---

### 5. Fire-Fighting Measures

#### Extinguishing media

Suitable extinguishing media:  
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:  
water jet

#### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

#### Advice for fire-fighters

Protective equipment for fire-fighting:  
Wear a self-contained breathing apparatus.

#### Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

#### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

#### Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.  
For large amounts: Pump off product.

---

### 7. Handling and Storage

#### Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

#### Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: tinned carbon steel (Tinplate)

# Safety Data Sheet

## WABO SILICONE SEAL PART A

Revision date : 2015/09/10  
Version: 3.0

Page: 5/10  
(30574095/SDS\_GEN\_CA/EN)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

Toluene	OSHA PEL	max. conc. 500 ppm ; CLV 300 ppm ; TWA value 200 ppm ; STEL value 150 ppm 560 mg/m <sup>3</sup> ; TWA value 100 ppm 375 mg/m <sup>3</sup> ;
	ACGIH TLV	TWA value 20 ppm ;
Limestone	OSHA PEL	PEL 5 mg/m <sup>3</sup> Respirable fraction ; PEL 15 mg/m <sup>3</sup> Total dust ; TWA value 15 mg/m <sup>3</sup> Total dust ; TWA value 5 mg/m <sup>3</sup> Respirable fraction ;

#### **Advice on system design:**

No applicable information available.

#### Personal protective equipment

##### **Respiratory protection:**

Wear a NIOSH-certified (or equivalent) respirator as necessary.

##### **Hand protection:**

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

##### **Eye protection:**

Safety glasses with side-shields.

##### **Body protection:**

Impermeable protective clothing

##### **General safety and hygiene measures:**

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

### 9. Physical and Chemical Properties

Form:	liquid
Odour:	aromatic, slight odour
Odour threshold:	No applicable information available.
Colour:	white
pH value:	not applicable
Melting point:	No applicable information available.
boiling temperature:	approx. 110 °C
Sublimation point:	No applicable information available.
Flash point:	approx. 93.34 °C
Flammability:	not highly flammable

# Safety Data Sheet

## WABO SILICONE SEAL PART A

Revision date : 2015/09/10  
Version: 3.0

Page: 6/10  
(30574095/SDS\_GEN\_CA/EN)

Vapour pressure:	No applicable information available.
Density:	approx. 1.08 g/cm <sup>3</sup> ( 20 °C)
Relative density:	approx. 1.08
Vapour density:	No applicable information available.
Partitioning coefficient n-octanol/water (log Pow):	No applicable information available.
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No applicable information available.
Viscosity, kinematic:	No applicable information available.
Solubility in water:	( 20 °C) insoluble
Miscibility with water:	( 20 °C) not soluble
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

---

## 10. Stability and Reactivity

### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Corrosion to metals:

Corrosive effects to metal are not anticipated.

### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

### Conditions to avoid

See MSDS section 7 - Handling and storage.

### Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

### Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

---

## 11. Toxicological information

### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

# Safety Data Sheet

## WABO SILICONE SEAL PART A

Revision date : 2015/09/10  
Version: 3.0

Page: 7/10  
(30574095/SDS\_GEN\_CA/EN)

### Acute Toxicity/Effects

#### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. Based on available Data, the classification criteria are not met. The product has not been tested. The statement has been derived from the properties of the individual components.

#### Oral

No applicable information available.

#### Inhalation

No applicable information available.

#### Dermal

No applicable information available.

#### Assessment other acute effects

No applicable information available.

#### Irritation / corrosion

Assessment of irritating effects: No irritation is expected under intended use and appropriate handling. Based on available Data, the classification criteria are not met.

#### Sensitization

Assessment of sensitization: May cause allergic skin reaction.

### Chronic Toxicity/Effects

#### Repeated dose toxicity

Assessment of repeated dose toxicity: An effect on the central nervous system cannot be excluded after repeated exposure.

#### Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

#### Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

#### *Information on: Titanium dioxide*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.*

-----

#### Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

#### Teratogenicity

# Safety Data Sheet

## WABO SILICONE SEAL PART A

Revision date : 2015/09/10  
Version: 3.0

Page: 8/10  
(30574095/SDS\_GEN\_CA/EN)

Assessment of teratogenicity: May cause harm to the unborn child.

*Information on: Toluene*

*Assessment of teratogenicity: Indications of possible developmental toxicity/teratogenicity were seen in animal studies.*

### Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

### **Symptoms of Exposure**

skin irritation, allergic symptoms

---

## 12. Ecological Information

### **Toxicity**

Aquatic toxicity

Assessment of aquatic toxicity:

Based on available Data, the classification criteria are not met. There is a high probability that the product is not acutely harmful to aquatic organisms.

Acutely harmful for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

### **Persistence and degradability**

Assessment biodegradation and elimination (H<sub>2</sub>O)

Inherently biodegradable. The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

### **Bioaccumulative potential**

Assessment bioaccumulation potential

Discharge into the environment must be avoided.

### **Mobility in soil**

Assessment transport between environmental compartments

No data available.

### **Additional information**

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

## 13. Disposal considerations

**Waste disposal of substance:**



# Safety Data Sheet

## WABO SILICONE SEAL PART A

Revision date : 2015/09/10  
Version: 3.0

Page: 9/10  
(30574095/SDS\_GEN\_CA/EN)

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

### Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

---

## 14. Transport Information

### Land transport

TDG

Not classified as a dangerous good under transport regulations

### Sea transport

IMDG

Not classified as a dangerous good under transport regulations

### Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

---

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical DSL, CA released / listed

### According to Controlled Products Regulations (CPR) (SOR/88-66)

#### WHMIS classification:

D2A: Materials Causing Other Toxic Effects - Very  
toxic material



D2B: Materials Causing Other Toxic Effects - Toxic  
material



**THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.**

---

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations  
SDS Prepared on: 2015/09/10

# Safety Data Sheet

## WABO SILICONE SEAL PART A

Revision date : 2015/09/10

Version: 3.0

Page: 10/10

(30574095/SDS\_GEN\_CA/EN)

---

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

END OF DATA SHEET