

# Safety Data Sheet

## WABO Foam Seal Bonder- Beige PTB

Revision date : 2015/11/09

Version: 3.1

Page: 1/9

(30571798/SDS\_GEN\_US/EN)

### 1. Identification

**Product identifier used on the label**

## WABO Foam Seal Bonder- Beige PTB

**Recommended use of the chemical and restriction on use**

Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

**Details of the supplier of the safety data sheet**

Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

**Emergency telephone number**

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

**Other means of identification**

Chemical family: No data available.

---

### 2. Hazards Identification

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

**Classification of the product**

Acute Tox.	4 (oral)	Acute toxicity
Skin Corr./Irrit.	1B	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Skin Sens.	1A	Skin sensitization
Repr.	2 (fertility)	Reproductive toxicity
Aquatic Acute	3	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

**Label elements**

# Safety Data Sheet

## WABO Foam Seal Bonder- Beige PTB

Revision date : 2015/11/09

Version: 3.1

Page: 2/9

(30571798/SDS\_GEN\_US/EN)

Pictogram:



Signal Word:

Danger

Hazard Statement:

H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H361	Suspected of damaging fertility.
H402	Harmful to aquatic life.
H412	Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P260	Do not breathe dust or mist.
P273	Avoid release to the environment.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P272	Contaminated work clothing should not be allowed out of the workplace.
P270	Do not eat, drink or smoke when using this product.
P264	Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P310	Immediately call a POISON CENTER or doctor/physician.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303 + P361 + P352	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301 + P330 + P331	IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container to hazardous or special waste collection point.
------	---

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

#### Labeling of special preparations (GHS):

The following percentage of the mixture consists of component(s) with unknown hazards regarding the acute toxicity: 29 % oral

# Safety Data Sheet

## WABO Foam Seal Bonder- Beige PTB

Revision date : 2015/11/09  
Version: 3.1

Page: 3/9  
(30571798/SDS\_GEN\_US/EN)

### 3. Composition / Information on Ingredients

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
100-51-6	>= 20.0 - < 50.0%	Benzyl alcohol
1317-65-3	>= 15.0 - < 20.0%	Limestone
2855-13-2	>= 10.0 - < 20.0%	3-aminomethyl-3,5,5-trimethylcyclohexylamine
80-05-7	>= 5.0 - < 15.0%	bisphenol A
1477-55-0	>= 5.0 - < 15.0%	1,3-Benzenedimethanamine
25068-38-6	>= 5.0 - < 7.0%	bisphenol A-epichlorohydrin resin

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

##### If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

##### If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

##### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

##### If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

#### Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Hazards: No applicable information available.

#### Indication of any immediate medical attention and special treatment needed

##### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

### 5. Fire-Fighting Measures

#### Extinguishing media

# Safety Data Sheet

## WABO Foam Seal Bonder- Beige PTB

Revision date : 2015/11/09

Version: 3.1

Page: 4/9

(30571798/SDS\_GEN\_US/EN)

---

Suitable extinguishing media:

carbon dioxide, dry powder, foam, water spray

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, nitrogen oxides, fumes/smoke, carbon black, corrosive gases/vapours

### Advice for fire-fighters

Protective equipment for fire-fighting:

Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

---

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Handle in accordance with good building materials hygiene and safety practice.

### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

### Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

---

## 7. Handling and Storage

### Precautions for safe handling

Keep away from sources of ignition - No smoking. Keep container tightly sealed. Handle and open container with care.

Protection against fire and explosion:

The product does not contribute to the spreading of flames, nor is it self combustible, not explosive.

### Conditions for safe storage, including any incompatibilities

No applicable information available.

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight. Store protected against freezing.

---

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

# Safety Data Sheet

## WABO Foam Seal Bonder- Beige PTB

Revision date : 2015/11/09

Page: 5/9

Version: 3.1

(30571798/SDS\_GEN\_US/EN)

Limestone	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;
1,3-Benzenedimethanamine	OSHA PEL	CLV 0.1 mg/m3 ; SKIN_FINAL ; The substance can be absorbed through the skin.
	ACGIH TLV	CLV 0.1 mg/m3 ; Skin Designation ; The substance can be absorbed through the skin.

### Advice on system design:

No applicable information available.

### Personal protective equipment

#### Respiratory protection:

Wear a NIOSH-certified (or equivalent) respirator as necessary.

#### Hand protection:

Wear chemical resistant protective gloves., Protective glove selection must be based on the user's assessment of the workplace hazards.

#### Eye protection:

Tightly fitting safety goggles (chemical goggles) and face shield.

#### Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. head protection, apron, protective boots, chemical-protection suit.

#### General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

---

## 9. Physical and Chemical Properties

Form:	paste
Odour:	ammonia-like
Odour threshold:	No applicable information available.
Colour:	beige
pH value:	The product has not been tested.
Melting point:	No applicable information available.
Boiling point:	The product has not been tested.
Sublimation point:	No applicable information available.
Flash point:	110 °C
Flammability:	not determined
Lower explosion limit:	No data available.
Upper explosion limit:	No data available.
Autoignition:	No data available.
Vapour pressure:	No data available.
Density:	1.17 g/cm3

# Safety Data Sheet

## WABO Foam Seal Bonder- Beige PTB

Revision date : 2015/11/09

Version: 3.1

Page: 6/9

(30571798/SDS\_GEN\_US/EN)

Relative density:	No applicable information available.
Vapour density:	No data available.
Partitioning coefficient n-octanol/water (log Pow):	No data available.
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic:	No data available.
Viscosity, kinematic:	No applicable information available.
Solubility (quantitative):	No applicable information available.
Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

#### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

Reacts with amines.

#### Conditions to avoid

See MSDS section 7 - Handling and storage.

#### Incompatible materials

strong oxidizing agents, strong bases, strong acids

#### Hazardous decomposition products

Decomposition products:  
carbon oxides, nitrogen oxides

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: Harmful if swallowed.

##### Oral

Type of value: ATE

Value: 1,270 mg/kg

# Safety Data Sheet

## WABO Foam Seal Bonder- Beige PTB

Revision date : 2015/11/09  
Version: 3.1

Page: 7/9  
(30571798/SDS\_GEN\_US/EN)

### Inhalation

No applicable information available.

### Dermal

No applicable information available.

### Assessment other acute effects

No applicable information available.

### Irritation / corrosion

Assessment of irritating effects: Causes burns.

### Sensitization

Assessment of sensitization: May cause allergic skin reaction.

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: No applicable information available.

### Genetic toxicity

Assessment of mutagenicity: No applicable information available.

### Reproductive toxicity

Assessment of reproduction toxicity: Possible risk of impaired fertility.

### *Information on: bisphenol A*

*Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect.*

## **Symptoms of Exposure**

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

---

## **12. Ecological Information**

### **Toxicity**

#### Aquatic toxicity

Assessment of aquatic toxicity:

Acutely harmful for aquatic organisms.

### **Additional information**

Other ecotoxicological advice:

May cause long-term adverse effects in the aquatic environment.

---

## **13. Disposal considerations**

### **Waste disposal of substance:**

Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.

# Safety Data Sheet

## WABO Foam Seal Bonder- Beige PTB

Revision date : 2015/11/09

Version: 3.1

Page: 8/9

(30571798/SDS\_GEN\_US/EN)

### Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

## 14. Transport Information

### Land transport

USDOT

Hazard class: 8  
Packing group: III  
ID number: UN 2735  
Hazard label: 8  
Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (contains ISOPHORONEDIAMINE, M-PHENYLENEBIS(METHYLAMINE))

### Sea transport

IMDG

Hazard class: 8  
Packing group: III  
ID number: UN 2735  
Hazard label: 8  
Marine pollutant: NO  
Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (contains ISOPHORONEDIAMINE, M-PHENYLENEBIS(METHYLAMINE))

### Air transport

IATA/ICAO

Hazard class: 8  
Packing group: III  
ID number: UN 2735  
Hazard label: 8  
Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (contains ISOPHORONEDIAMINE, M-PHENYLENEBIS(METHYLAMINE))

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical TSCA, US released / listed

**EPCRA 311/312 (Hazard categories):** Acute; Chronic

#### EPCRA 313:

<u>CAS Number</u>	<u>Chemical name</u>
80-05-7	bisphenol A

### State regulations

#### State RTK

<u>State RTK</u>	<u>CAS Number</u>	<u>Chemical name</u>
PA	1477-55-0	1,3-Benzenedimethanamine
	100-51-6	Benzyl alcohol
	1317-65-3	Limestone



# Safety Data Sheet

## WABO Foam Seal Bonder- Beige PTB

Revision date : 2015/11/09

Page: 9/9

Version: 3.1

(30571798/SDS\_GEN\_US/EN)

MA	80-05-7	bisphenol A
	1477-55-0	1,3-Benzenedimethanamine
	100-51-6	Benzyl alcohol
	1317-65-3	Limestone
NJ	80-05-7	bisphenol A
	1477-55-0	1,3-Benzenedimethanamine
	2855-13-2	3-aminomethyl-3,5,5-trimethylcyclohexylamine
	80-05-7	bisphenol A
	1317-65-3	Limestone

### CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

### NFPA Hazard codes:

Health : 3      Fire: 1      Reactivity: 0      Special:

### HMIS III rating

Health: 3<sup>+</sup>      Flammability: 1      Physical hazard: 0

## 16. Other Information

### SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2015/11/09

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET