



Design Features

- Accommodates up to 13" of movement
- Low profile system
- Designed to prevent debris build-up and allow for a smooth ride

Model	"A"		"B"		"C"		"D"							
	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.						
	inches	mm	inches	mm	inches	mm	inches	mm						
400A	21 1/4	540	25 1/4	641	17 5/8	448	21 5/8	549	2	51	6	152	2 1/8	54
650	25 1/4	641	31 3/4	806	21	533	27 1/2	699	1 1/2	38	8	203	3	76
900	30 7/8	784	39 7/8	1013	26 1/2	673	35 1/2	902	1 3/4	44	10 3/4	273	3 3/4	95
1300	41	1041	54	1372	36	914	49	1245	2	51	15	381	5	127

PROJECT NAME: -

PROJECT LOCATION: -

DRAWING DESCRIPTION:

WaboTransFlex

DATE: 10/10/16

MODEL: 400A-1300

BASF
We create chemistry

Watson Bowman Acme Corp.
95 Pineview Drive Amherst, NY 14228
phone: (716) 691-7566 fax: (716) 691-9239
www.wbacorp.com

**Watson
Bowman
Acme**

Information provided herein, including but not limited to, any drawing, design, photograph, graphic, or statement(s) ("Materials") are proprietary and the property of Watson Bowman Acme Corporation ("Company"). Reproduction, translation, or reduction to any electronic medium or machine readable form, in whole or part, is strictly prohibited, except for the express purpose for which it has been furnished, without prior written consent of Company. All Materials contained herein are provided by Company for information purposes only. Company reserves the right to amend or withdraw any information contained in the Materials without notice. All technical or other advice by Company, whether verbal or written, concerning products, or the use of products in specific situations ("Advice") is given by Company and is used at the Users own risk.

REVISION NO:
2

SHEET NO:
1

DRAWING NO:
C-21396